

View Online at <https://aerobasegroup.com/nsn/5930-00-583-8633>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Salt spray resistant

Overall Length:

0.516 inches

Overall Height:

1.203 inches

Overall Width:

0.266 inches

Bushing Length:

0.250 inches

Body Length:

Between 0.500 inches and 0.532 inches

Body Width:

Between 0.250 inches and 0.282 inches

Body Height:

0.328 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Height:

0.422 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 50.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0