

View Online at <https://aerobasegroup.com/nsn/5930-00-583-8861>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.489 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Round

Actuator Diameter:

0.092 inches

Actuator Height:

0.020 inches

Actuator Free Position Height:

0.365 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Nimitz class cvn, spruance class d (963), forrestal class cv, oliver perry class ffg, wasp class lhd, sturgeon class ssn(637), missile minuteman lgm-30, aircraft phantom f-4, stratofortress b-52, hercules c-130, delta dart f-106, f-111, galaxy c-5, starlifter c-141, eagle f-15, awacs e-3a, helicopter super jolly h-53, sof/hh-53h pave low, missile maverick agm-65a, 485l tacs, cobra dan sys fps-108, joint surveillance sys(jss)/region ops ctrl center(rocc), simulator f-111, f-4, communications program combat theater(tri-tac) 478i, support equipment t-37 aircraft, support equipment t-38 aircraft, aircraft (ac-130h, mc-130h, ec-130e, hc-

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

Criticality Code Justification:

Feat

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0