

View Online at <https://aerobasegroup.com/nsn/5930-00-584-3156>

Hazardous Locations/environmental Protection:

Corrosion resistant and dustproof and vibration resistant and watertight

Overall Length:

4.750 inches

Overall Height:

5.344 inches

Overall Width:

1.906 inches

Body Height:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.625 inches

Longest Vertical Distance Between Mounting Centers:

2.875 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

45.00 pounds per square inch

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.00/+30.00 actuation point pounds per square inch and +0.00/+30.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut and internal deactuation point hex nut

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Beveled, butt weld single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0