

View Online at <https://aerobasegroup.com/nsn/5930-00-584-3460>

**Overall Length:**

6.300 inches

**Overall Height:**

2.720 inches

**Overall Width:**

4.750 inches

**Unthreaded Mounting Hole Diameter:**

0.265 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Longest Vertical Distance Between Mounting Centers:**

3.100 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, plug

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+750.00/+1250.00 actuation point pounds per square inch and +500.00/+1050.00 deactuation point pounds per square inch

**Contact Stimulus Rating:**

800.00 actuation point pounds per square inch and 600.00 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0