NSN 5930-00-584-3487

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-584-3487

Overall Length:
6.300 inches
Overall Height:
2.720 inches
Overall Width:
4.750 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Longest Vertical Distance Between Mounting Centers:
3.100 inches
Pressure Switch Type:
Gage
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.500 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, plug
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+1425.00/+2325.00 actuation point pounds per square inch and +1135.00/+2035.00 deactuation point pounds per square inch
Contact Stimulus Rating:
1500.00 actuation point pounds per square inch and 1210.00 deactuation point pounds per square inch
Contact Voltage Rating In Volts:
120.0 ac at sea level single voltage

Pressure Connector Type:
Plain, threaded internal single connection

NSN 5930-00-584-3487Pressure Switch - Page 2 of 2



Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0