## NSN 5930-00-585-5888

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-585-5888 **Overall Length:** 3.760 inches **Power Cable Length:** Between 59.000 inches and 61.000 inches Dc Voltage Rating: 28.0 volts **Overall Diameter:** 1.380 inches **Actuation Method:** Buoyancy **Electrical Connection Type:** Cable **Internal Battery Accommodation:** Not included **Current Rating At Maximum Rated Voltage:** 500.0 milliamperes load Float Quantity: 1 **Operating Tempurature Rating:** Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit **Mounting Method:** Thread **Mounting Position:** Vertical **Contact Arrangement:** Spst, normally open Relay: Included **Liquid Type For Which Designed:** Aircraft fuel Aircraft Fuel For Which Designed: Aircraft Fuel Grade Specificationification: Mil-g-5572, mil-j-5624 Aircraft Fuel Grade: Grades 80/87, 91/96, 100/130, grades jp-4, jp-5 Aircraft Fuel Grade Specificationific Gravity Rating:

Not rated Float Effective Travel: 0.375 inches

**Mounting Dimensions:** 

Mtg by 9/16-18 unf thd connection

## NSN 5930-00-585-5888

Liquid Level Switch - Page 2 of 2



Tank	Insertion	Lenath:

2.360 inches

**Fsc Application Data:** 

Fuel system, engine, aircraft

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

T109-d

Mil-std (military Standard):

Mil-g-5572 spec.