# NSN 5930-00-587-4605

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-587-4605

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.750 inches

### **Overall Height:**

1.500 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.438 inches at 9:00 o'clock

# Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

2 single section rear

#### **Throw Quantity:**

5 single section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# **Thread Size:**

0.375 inches single mounting facility

# Contact Voltage Rating In Volts:

15.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

5 single actuator

# Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes single section front

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-587-4605

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 2.0 amperes resistive load dc at sea level **Special Features:** W/locking device **Precious Material And Location:** Rotor blades and terminal surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0