

View Online at <https://aerobasegroup.com/nsn/5930-00-588-9619>

**Overall Length:**

2.406 inches

**Overall Height:**

4.000 inches

**Overall Width:**

1.937 inches

**Unthreaded Mounting Hole Diameter:**

0.218 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.436 inches

**Longest Vertical Distance Between Mounting Centers:**

1.436 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Base and unthreaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.60/+15.00 actuation point pounds per square inch and +0.50/+14.50 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point knob with scale and external actuation point knob with scale

**Contact Stimulus Rating:**

10.00 actuation point pounds per square inch gage and 9.50 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Inverted flare, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0