

View Online at <https://aerobasegroup.com/nsn/5930-00-588-9619>

Overall Length:

2.406 inches

Overall Height:

4.000 inches

Overall Width:

1.937 inches

Unthreaded Mounting Hole Diameter:

0.218 inches

Longest Horizontal Distance Between Mounting Centers:

1.436 inches

Longest Vertical Distance Between Mounting Centers:

1.436 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.60/+15.00 actuation point pounds per square inch and +0.50/+14.50 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Stimulus Rating:

10.00 actuation point pounds per square inch gage and 9.50 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0