NSN 5930-00-588-9686

Pressure Switch - Page 1 of 2

30.0 dc at sea level second voltage



View Online at https://aerobasegroup.com/nsn/5930-00-588-9686

Thread Class:
3b single pressure connection
Inside Diameter:
0.190 inches single connection
Thread Length:
0.563 inches single pressure connection
Overall Length:
3.156 inches
Body Diameter:
1.812 inches
Body Length:
2.062 inches
Overall Diameter:
1.812 inches
Distance Between Mounting Facility Centers:
1.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and threaded stud
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
32 single pressure connection
Contact Action Stimulus:
Decrease
Thread Size:
0.190 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
4.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
95.75 actuation point pounds per square inch gage and 5.00 differential point pounds per square inch gage
Contact Voltage Rating In Volts:

NSN 5930-00-588-9686

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0