

View Online at <https://aerobasegroup.com/nsn/5930-00-588-9940>

Thread Class:

3a single pressure connection

Overall Length:

2.625 inches

Overall Diameter:

1.218 inches

Pressure Switch Type:

Gage

Mounting Method:

Outlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

220.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

1000.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

155.00 actuation point pounds per square inch gage and 200.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0