

View Online at <https://aerobasegroup.com/nsn/5930-00-589-0105>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.490 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.560 inches

**Actuator Roller Diameter:**

0.187 inches

**Actuator Roller Width:**

0.125 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

70.0 grams

**Switch Actuating Force:**

40.0 grams

**Actuator Movement:**

Between 0.085 pretravel inches and 0.018 overtravel inches and 0.019 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0