

View Online at <https://aerobasegroup.com/nsn/5930-00-592-0437>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.310 inches

Overall Height:

2.310 inches

Overall Width:

2.160 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.620 inches single actuator

Nonturn Device Radius:

0.530 inches at 9:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 9:00 o'clock

Operating Temperature Range:

-25.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 4th section rear

Throw Quantity:

16 1st section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0