NSN 5930-00-592-0768

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-00-592-0768

2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.710 inches **Overall Height:** 1.484 inches **Overall Width:** 1.438 inches **Shaft Diameter:** 0.250 inches single actuator Shaft Length: 2.250 inches single actuator **Nonturn Device Radius:** 0.438 inches at 9: 00 o'clock **Individual Section Quantity:** 2 **Knob Manufacturer Code:** 71590 **Knob Manufacturer Part Number:** P-120 **Nonturn Device Type:** Tab at 9: 00 o'clock **Operating Tempurature Range:** -65.0/+175.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 5 each section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:**

5 single actuator

6.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

NSN 5930-00-592-0768Rotary Switch - Page 2 of 2



Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.5 amperes resistive load highest dc voltage rating at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0