NSN 5930-00-592-1178

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-592-1178

Hole mounted			
Hazardous Locations/environmental Protection:			
Dustproof			
Center To Center Distance Between Mounting Facilities Parallel To Length:			
0.500 inches			
Body Length:			
0.850 inches			
Body Width:			
0.320 inches			
Body Height:			
0.688 inches			
Unthreaded Mounting Hole Diameter:			
0.112 inches			
Actuator Style:			
Round			
Actuator Diameter:			
0.109 inches			
Actuator Free Position Height:			
0.307 inches			
Maximum Voltage Rating In Volts:			
28.0 dc			
Inclosure Type:			
Fully enclosed			
Mounting Method:			
Threaded hole			
Features Provided:			
Actuator seal			
Nonpile-up Contact Arrangement:			
1 pole, single throw, both positions maintained single switch unit			
Switch Release Force:			
8.0 ounces			
Switch Actuating Force:			
24.0 ounces			
Actuator Movement:			
Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches			
Contact Load Current Rating At Maximum Rated Voltage:			
10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc			
Special Features:			
Wire lead terminls are 6 in. Lg			
Terminal Type And Quantity:			
2 wire lead			

NSN 5930-00-592-1178

Sensitive Switch - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0