## NSN 5930-00-592-3645

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-592-3645

| Body Style:   |
|---|
| Hole mounted  |
| Hazardous Locations/environmental Protection:   |
| Watertight  |
| Overall Length:   |
| 7.188 inches  |
| Overall Height:   |
| 2.469 inches  |
| Overall Width:  |
| 2.250 inches  |
| Case Material:  |
| Metal   |
| Actuator Style:   |
| Roller plunger  |
| Actuator Free Position Height:  |
| 1.906 inches  |
| Actuator Roller Diameter:   |
| 1.000 inches  |
| Actuator Roller Width:  |
| 0.250 inches  |
| Housing Height:   |
| 2.312 inches  |
| Housing Length:   |
| 4.750 inches  |
| Housing Width:  |
| 2.250 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length:     |
| 4.219 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:      |
| 1.719 inches  |
| Maximum Voltage Rating In Volts:  |
| 240.0 ac and 240.0 dc   |
| Inclosure Type:   |
| Fully enclosed  |
| Nonpile-up Contact Arrangement:   |
| 3 two circuit, double break/double make, both positions maintained single switch unit |
| Switch Release Force:   |
| 144.0 ounces  |
| Switch Actuating Force:   |
| 288.0 ounces  |
| Contact Load Current Rating At Maximum Rated Voltage:                                 |

15.000 amperes resistive dc and 15.000 amperes resistive ac

## NSN 5930-00-592-3645

Sensitive Switch - Page 2 of 2



| Terminal Type And Quantity | y: |
|----------------------------|----|
|----------------------------|----|

12 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0