# NSN 5930-00-592-3684

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-592-3684

# Thread Class:

2b single threaded bushing

# Thread Length:

0.375 inches single threaded bushing

# **Overall Length:**

3.171 inches

# Body Diameter:

0.250 inches

# Body Length:

2.062 inches

# Bulb Length:

1.687 inches

# Bulb Diameter:

0.250 inches

# Tempurature Sensing Element Type:

Bulb

# Width Across Flats:

0.500 inches

### **Operating Tempurature Rating:**

Between -100.0 degrees fahrenheit and 348.0 degrees fahrenheit

#### **Mounting Method:**

Threaded bushing

#### **Features Provided:**

Hermetically sealed case

#### Thready Qty Per Inch (tpi):

24 single threaded bushing

#### **Contact Action Stimulus:**

Increase

#### Thread Size:

0.375 inches single threaded bushing

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

#### **Terminal Type:**

Wire lead

#### **Contact Load Current Rating:**

1.0 amperes resistive load second voltage

#### Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

#### **Contact Adjustment Range:**

-50.00/+500.00 actuation point degrees fahrenheit and -50.00/+500.00 deactuation point degrees fahrenheit

#### Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

# NSN 5930-00-592-3684

Thermostatic Switch - Page 2 of 2



#### **Contact Stimulus Rating:**

248.00 actuation point degrees fahrenheit and 247.00 deactuation point degrees fahrenheit

#### **Contact Voltage Rating In Volts:**

32.0 dc at sea level second voltage

#### **Frequency In Hertz:**

60.0 first voltage

#### Media For Which Designed:

Gas or liquid

#### Precious Material And Location:

Terminal surfaces silver

#### **Precious Material:**

Silver

#### Style Designator:

Cylindrical w/flange

#### **Thread Series Designator:**

Unf single threaded bushing

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A048b0