

View Online at <https://aerobasegroup.com/nsn/5930-00-593-9295>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Dust resistant and watertight

**Overall Length:**

3.500 inches

**Overall Height:**

8.312 inches

**Overall Width:**

2.500 inches

**Body Height:**

3.500 inches

**Unthreaded Mounting Hole Diameter:**

0.266 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.719 inches

**Longest Vertical Distance Between Mounting Centers:**

2.719 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

375.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

6.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+5.00/+40.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level fourth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0