

View Online at <https://aerobasegroup.com/nsn/5930-00-594-3039>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.350 inches single mounting facility

**Overall Length:**

2.040 inches

**Overall Height:**

1.120 inches

**Overall Width:**

0.910 inches

**First Flat Length:**

0.430 inches single actuator

**Flat Height:**

0.093 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.910 inches single actuator

**Nonturn Device Radius:**

0.250 inches at 3: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Shaft Flat/slot Angular Location:**

270.0 degrees from nonturn device single actuator

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, one position momentary each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Turret

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Detent Rotational Torque Range:**

+1.200/+2.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0