NSN 5930-00-595-9276

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-595-9276

Body Style:
Hole mounted
Overall Length:
1.380 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.600 inches
Overall Width:
0.742 inches
Body Length:
1.380 inches
Body Width:
0.742 inches
Body Height:
0.975 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.142 inches
Actuator Length:
0.267 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.687 inches
Actuator Roller Diameter:
0.211 inches
Actuator Roller Width:
0.156 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
12.0 ounces

48.0 ounces

Actuator Movement:

Switch Actuating Force:

Between 0.065 pretravel inches and 0.125 overtravel inches and 0.050 differential inches

NSN 5930-00-595-9276

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

Wire leads terminals 36 in. Lg

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0