

View Online at <https://aerobasegroup.com/nsn/5930-00-597-4964>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 0.828 inches and 0.890 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.370 inches and 0.380 inches

**Overall Height:**

0.605 inches

**Overall Width:**

Between 0.240 inches and 0.260 inches

**Body Length:**

0.781 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.470 inches and 0.490 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Length:**

0.692 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.133 inches

**Actuator Free Position Height:**

0.465 inches

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 grams

**Switch Actuating Force:**

24.0 grams

**Actuator Movement:**

Between 0.465 pretravel inches and 0.040 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

100.000 milliamperes resistive ac

**Special Features:**

One mtg slot 0.088 in. By 0.098 in.

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0