

View Online at <https://aerobasegroup.com/nsn/5930-00-597-4964>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 0.828 inches and 0.890 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Overall Height:

0.605 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Body Length:

0.781 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.470 inches and 0.490 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.692 inches

Actuator Style:

Leaf

Actuator Width:

0.133 inches

Actuator Free Position Height:

0.465 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 grams

Switch Actuating Force:

24.0 grams

Actuator Movement:

Between 0.465 pretravel inches and 0.040 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive ac

Special Features:

One mtg slot 0.088 in. By 0.098 in.

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0