## NSN 5930-00-597-5057

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-597-5057

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
8.157 inches
Overall Height:
6.000 inches
Overall Width:
4.750 inches
First Flat Length:
1.125 inches single actuator
Flat Height:
0.250 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.563 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
6
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
2 each section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
600.0 ac at sea level
Mounting Facility Pattern:

Four position rectangular single mounting facility

## **NSN 5930-00-597-5057** Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0