

View Online at <https://aerobasegroup.com/nsn/5930-00-599-5527>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

3.875 inches

Overall Width:

4.250 inches

Body Length:

4.250 inches

Body Width:

4.250 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical box connector

Contact Action Stimulus:

Increase

Proof Pressure:

10000.00 pounds per square inch

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+200.00/+2000.00 actuation point pounds per square inch and +160.00/+1830.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point dial and external deactuation point dial

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0