

View Online at <https://aerobasegroup.com/nsn/5930-00-599-5527>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Height:**

3.875 inches

**Overall Width:**

4.250 inches

**Body Length:**

4.250 inches

**Body Width:**

4.250 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.625 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical box connector

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

10000.00 pounds per square inch

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+200.00/+2000.00 actuation point pounds per square inch and +160.00/+1830.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point dial and external deactuation point dial

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0