

View Online at <https://aerobasegroup.com/nsn/5930-00-599-9647>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

10.000 inches

**Overall Height:**

9.625 inches

**Overall Width:**

6.750 inches

**First Flat Length:**

1.375 inches single actuator

**Flat Height:**

0.438 inches single actuator

**Shaft Diameter:**

0.625 inches single actuator

**Shaft Length:**

1.687 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.531 inches single mounting facility

**Individual Section Quantity:**

3

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

A

**Longest Horizontal Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

600.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

200.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0