## NSN 5930-00-600-1633

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-600-1633
Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.553 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Round

**Actuator Height:** 

0.100 inches

**Actuator Free Position Height:** 

0.365 inches

**Maximum Voltage Rating In Volts:** 

250.0 ac and 30.0 dc

**Inclosure Type:** 

Fully enclosed

**Mounting Method:** 

Unthreaded hole

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:** 

1.0 ounces

**Switch Actuating Force:** 

7.0 ounces

**Actuator Movement:** 

Between 0.020 pretravel inches and 0.030 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

3.000 amperes resistive dc and 2.000 amperes inductive dc and 2.000 amperes motor dc and 5.000 amperes resistive ac

## NSN 5930-00-600-1633

Sensitive Switch - Page 2 of 2



Terminal Type Aı	nd Quantity:
------------------	--------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0