NSN 5930-00-600-1633

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-600-1633
Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.553 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Round

Actuator Height:

0.100 inches

Actuator Free Position Height:

0.365 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.030 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 2.000 amperes inductive dc and 2.000 amperes motor dc and 5.000 amperes resistive ac

NSN 5930-00-600-1633

Sensitive Switch - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0