

View Online at <https://aerobasegroup.com/nsn/5930-00-600-1633>

**Body Style:**

Hole mounted

**Overall Length:**

0.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

0.553 inches

**Overall Width:**

0.250 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.359 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Height:**

0.100 inches

**Actuator Free Position Height:**

0.365 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.030 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 2.000 amperes inductive dc and 2.000 amperes motor dc and 5.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0