

View Online at <https://aerobasegroup.com/nsn/5930-00-601-0359>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

7.250 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

5.375 inches single actuator

**Overall Diameter:**

1.852 inches

**Nonturn Device Radius:**

0.375 inches at 10: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Slotted bushing at 10: 00 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 1st section front

**Throw Quantity:**

4 1st section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 1st section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Special Features:**

Sect. 1 rear and 2 front are blank, sect. 2 rear has 8 dummy terminals

**Style Designator:**

Circular wafer, bushing mount

**Test Data Document:**

09553-tc4428-393 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0