

View Online at <https://aerobasegroup.com/nsn/5930-00-601-4017>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.365 inches single mounting facility and 0.385 inches single mounting facility

**Overall Length:**

2.500 inches

**Shaft Diameter:**

0.220 inches single actuator and 0.280 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Overall Diameter:**

Between 1.250 inches and 1.300 inches

**Nonturn Device Radius:**

0.521 inches at 3: 00 o'clock and 0.541 inches at 3: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

6 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0