

View Online at <https://aerobasegroup.com/nsn/5930-00-601-4023>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

2.203 inches

Overall Width:

0.688 inches

Bushing Length:

0.562 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.812 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.143 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.922 inches and 1.984 inches

Actuator Roller Diameter:

Between 0.484 inches and 0.516 inches

Actuator Roller Width:

0.156 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 13.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 20.000 amperes resistive ac

Special Features:

One mtg hole shaped 0.141 in. W by 0.152 in. Lg

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0