

View Online at <https://aerobasegroup.com/nsn/5930-00-601-4023>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.938 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Overall Height:**

2.203 inches

**Overall Width:**

0.688 inches

**Bushing Length:**

0.562 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

0.812 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.143 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 1.922 inches and 1.984 inches

**Actuator Roller Diameter:**

Between 0.484 inches and 0.516 inches

**Actuator Roller Width:**

0.156 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 9.0 ounces and 13.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 20.000 amperes resistive ac

**Special Features:**

One mtg hole shaped 0.141 in. W by 0.152 in. Lg

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0