

View Online at <https://aerobasegroup.com/nsn/5930-00-602-1599>

Thread Class:

2b single pressure connection

Overall Length:

2.1875 inches

Overall Height:

2.6875 inches

Overall Width:

1.250 inches

Body Length:

1.4375 inches

Unthreaded Mounting Hole Diameter:

0.4375 inches

Distance Between Mounting Facility Centers:

Between 1.3125 inches and 1.750 inches

Capillary Tube Length:

15.0 inches

Bulb Length:

5.500 inches

Bulb Diameter:

0.375 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Threaded hole and unthreaded hole

Thready Qty Per Inch (tpi):

32 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.138 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

25.0 amperes resistive load second voltage and 10.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+55.00/+105.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point dial

Contact Stimulus Rating:

3.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

277.0 ac at sea level first voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Unc single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0