

View Online at <https://aerobasegroup.com/nsn/5930-00-603-6011>

**Overall Length:**

Between 1.040 inches and 1.080 inches

**Overall Height:**

Between 0.660 inches and 0.670 inches

**Body Diameter:**

Between 0.628 inches and 0.640 inches

**Mounting Slot Width:**

Between 0.113 inches and 0.127 inches

**Body Height:**

Between 0.305 inches and 0.325 inches

**Distance Between Mounting Facility Centers:**

Between 0.868 inches and 0.882 inches

**Tempurature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Decrease

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load third voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

25.00 actuation point degrees fahrenheit and 35.00 actuation point degrees fahrenheit and 45.00 deactuation point degrees fahrenheit and 55.00 deactuation point degrees fahrenheit and 20.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level third voltage

**Frequency In Hertz:**

400.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Test Data Document:**

96906-mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0