

View Online at <https://aerobasegroup.com/nsn/5930-00-603-6011>

Overall Length:

Between 1.040 inches and 1.080 inches

Overall Height:

Between 0.660 inches and 0.670 inches

Body Diameter:

Between 0.628 inches and 0.640 inches

Mounting Slot Width:

Between 0.113 inches and 0.127 inches

Body Height:

Between 0.305 inches and 0.325 inches

Distance Between Mounting Facility Centers:

Between 0.868 inches and 0.882 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

25.00 actuation point degrees fahrenheit and 35.00 actuation point degrees fahrenheit and 45.00 deactuation point degrees fahrenheit and 55.00 deactuation point degrees fahrenheit and 20.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Frequency In Hertz:

400.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Test Data Document:

96906-mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0