

View Online at <https://aerobasegroup.com/nsn/5930-00-603-8492>

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

Between 2.734 inches and 2.828 inches

Overall Height:

Between 1.246 inches and 1.328 inches

Overall Width:

Between 1.234 inches and 1.266 inches

First Flat Length:

0.422 inches single actuator and 0.454 inches single actuator

Flat Height:

0.202 inches single actuator and 0.234 inches single actuator

Shaft Diameter:

0.234 inches single actuator and 0.266 inches single actuator

Shaft Length:

0.859 inches single actuator and 0.891 inches single actuator

Nonturn Device Radius:

0.515 inches at 10:00 o'clock and 0.547 inches at 10:00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 10:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

12 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Shaft Flat/slot Angular Location:

65.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0