

View Online at <https://aerobasegroup.com/nsn/5930-00-604-3142>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

5.186 inches

Overall Height:

2.375 inches

Overall Width:

2.375 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.688 inches single actuator

Nonturn Device Radius:

0.484 inches at 12: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 12: 00 o'clock

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

16 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts, rotor and terminals silver

Precious Material:

Silver

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0