NSN 5930-00-605-2852

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-605-2852

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.906 inches
Overall Height:
2.688 inches
Overall Width:
5.000 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket
Thready Qty Per Inch (tpi):
18 single pressure connection
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Tab w/screw
Contact Load Current Rating:
3.4 amperes resistive load first voltage and 2.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+60.00/+350.00 actuation point pounds per square inch
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Frequency In Hertz:
60.0 single voltage
Thread Series Designator:
Npt single pressure connection
Shelf Life:

N/a

NSN 5930-00-605-2852

Pressure Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A048b0