

NSN 5930-00-605-6337 Rotary Switch - Page 1 of 2	Aero
View Online at https://aerobasegroup.com/nsn/5930-00-605-6337	
Thread Class:	
2a single mounting facility	
Thread Length:	
0.375 inches single mounting facility	
Overall Length:	
2.260 inches	
Overall Height:	
1.265 inches	
Overall Width:	
1.010 inches	
Shaft Diameter:	
0.249 inches single actuator and 0.251 inches single actuator	
Shaft Length:	
0.750 inches single actuator	
Nonturn Device Radius:	
0.375 inches at 3: 00 o'clock	
Individual Section Quantity:	
2	
Nonturn Device Type:	
Tab at 3: 00 o'clock	
Operating Tempurature Range:	
-65.0/+85.0 degrees celsius	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Polo Quantitus	

Pole Quantity:

1 each section front

Throw Quantity:

12 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

NSN 5930-00-605-6337

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0