

View Online at <https://aerobasegroup.com/nsn/5930-00-605-7597>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Case Material:

Metal

Actuator Length:

2.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.562 inches

Housing Length:

5.312 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.912 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

18

Thread Size:

0.313 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

358.0 ounces

Switch Actuating Force:

422.0 ounces

Actuator Movement:

Between 16.0 pretravel degrees and 6.0 overtravel degrees and 20.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0