

View Online at <https://aerobasegroup.com/nsn/5930-00-605-7597>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Case Material:**

Metal

**Actuator Length:**

2.500 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.250 inches

**Housing Height:**

2.562 inches

**Housing Length:**

5.312 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

4.219 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.912 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.313 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

358.0 ounces

**Switch Actuating Force:**

422.0 ounces

**Actuator Movement:**

Between 16.0 pretravel degrees and 6.0 overtravel degrees and 20.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0