NSN 5930-00-606-2934

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-606-2934

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.688 inches single actuator

Overall Diameter:

1.625 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.5 amperes resistive load dc at sea level

Precious Material And Location:

C0ntact surfaces silver

Precious Material:

Silver

NSN 5930-00-606-2934

Rotary Switch - Page 2 of 2



Sty	ما	D	20	in	n	2	ŧ۸	r	
JLY	ı	יש	င၁	ıу	••	а	ιυ	ш	

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0