NSN 5930-00-607-6335

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-607-6335

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
2.250 inches
Overall Height:
2.645 inches
Overall Width:
1.109 inches
Case Material:
Metal
Actuator Length:
1.310 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
Between 1.270 inches and 1.350 inches
Actuator Roller Diameter:
0.380 inches
Actuator Roller Width:
0.125 inches
Housing Length:
1.625 inches
Housing Width:
1.109 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.335 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.094 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
76.0 ounces
Actuator Movement:

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc

Between 0.083 pretravel inches and 0.187 overtravel inches and 0.040 differential inches

NSN 5930-00-607-6335

Sensitive Switch - Page 2 of 2



Two hole mounting

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0