NSN 5930-00-608-4564

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-608-4564

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Body Length:
1.406 inches
Body Width:
0.531 inches
Body Height:
1.406 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Actuator Style:
Round
Actuator Height:
0.400 inches
Actuator Free Position Height:
0.587 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Hermetically sealed
Hermetically sealed Mounting Method:
·
Mounting Method:
Mounting Method: Unthreaded hole
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi):
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size:
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement:
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Switch Release Force:
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Switch Release Force: 4.0 centimeter-grams
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Switch Release Force: 4.0 centimeter-grams Switch Actuating Force:
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Switch Release Force: 4.0 centimeter-grams Switch Actuating Force: 20.0 centimeter-grams
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Switch Release Force: 4.0 centimeter-grams Switch Actuating Force: 20.0 centimeter-grams Actuator Movement:
Mounting Method: Unthreaded hole Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Switch Release Force: 4.0 centimeter-grams Switch Actuating Force: 20.0 centimeter-grams Actuator Movement: 0.200 pretravel inches and 0.047 overtravel inches and 0.050 differential inches

Unc

NSN 5930-00-608-4564

Sensitive Switch - Page 2 of 2



Terminal	Туре	And	Quantity:
3 wire lea	ad		

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0