NSN 5930-00-608-9312

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-608-9312

| Overall Length: |
|---|
| 5.875 inches |
| Overall Height: |
| 5.968 inches |
| Overall Width: |
| 3.375 inches |
| Capillary Tube Length: |
| 84.000 inches |
| Bulb Length: |
| 4.750 inches |
| Bulb Diameter: |
| 0.250 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 3.375 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 2.438 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Base |
| Features Provided: |
| Tubing end seal connection |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Four position rectangular |
| Nonpile-up Contact Arrangement: |
| 2 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Threaded stud |
| Contact Load Current Rating: |
| 25.0 amperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point adjustable |
| Contact Adjustment Range: |
| +150.00/+250.00 actuation point degrees fahrenheit |
| Contact Adjustment Type: |
| Internal actuation point knob |
| Contact Voltage Rating In Volts: |
| 250.0 dc at sea level third voltage |
| Special Features: |
| Incl manualreset button and pilot light |

NSN 5930-00-608-9312

Thermostatic Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0