

View Online at <https://aerobasegroup.com/nsn/5930-00-609-8153>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.140 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.220 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.560 inches single actuator

**Overall Diameter:**

0.940 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

6 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0