NSN 5930-00-610-6025

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-610-6025		
Thread Class:		
2b		
Body Style:		
Hole mount		
Hazardous Locations/environmental Protection:		
Corrosion resistant and waterproof and dustproof		
Overall Length:		
Between 1.780 inches and 1.844 inches		
Center To Center Distance Between Mounting Facilities Parallel To Length:		
Between 1.566 inches and 1.582 inches		
Overall Height:		
Between 2.270 inches and 2.428 inches		
Overall Width:		
1.812 inches		
Body Diameter:		
Between 1.780 inches and 1.844 inches		
Body Height:		
Between 0.850 inches and 0.934 inches		
Actuator Diameter:		
Between 0.421 inches and 0.485 inches		
Actuator Height:		
Between 0.488 inches and 0.552 inches		
Actuator Color:		
Green single actuator		
Maximum Voltage Rating In Volts:		
110.0 ac and 30.0 dc		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Threaded hole		
Features Provided:		
Actuator seal		
Thready Qty Per Inch (tpi):		
32		
Thread Size:		
0.164 inches		
Nonpile-up Contact Arrangement:		
1 pole, single throw, normally open, double make, momentary action single switch unit		
Contact Load Current Rating At Maximum Rated Voltage:		
30.000 amperes resistive dc and 30.000 amperes resistive ac		
Thread Series Designator:		

Unc

NSN 5930-00-610-6025

Push Switch - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0