NSN 5930-00-610-6025

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-610-6025

Thread Class:
2b
Body Style:
Hole mount
Hazardous Locations/environmental Protection:
Corrosion resistant and waterproof and dustproof
Overall Length:
Between 1.780 inches and 1.844 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.566 inches and 1.582 inches
Overall Height:
Between 2.270 inches and 2.428 inches
Overall Width:
1.812 inches
Body Diameter:
Between 1.780 inches and 1.844 inches
Body Height:
Between 0.850 inches and 0.934 inches
Actuator Diameter:
Between 0.421 inches and 0.485 inches
Actuator Height:
Between 0.488 inches and 0.552 inches
Actuator Color:
Green single actuator
Maximum Voltage Rating In Volts:
110.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.164 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, double make, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
30.000 amperes resistive dc and 30.000 amperes resistive ac
Thread Series Designator:

Thread Series Designator:

Unc

NSN 5930-00-610-6025

Push Switch - Page 2 of 2



Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0