NSN 5930-00-613-1992

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-613-1992

Hazardous Locations/environmental Protection:
General purpose-nema type 1
Overall Length:
6.063 inches
Overall Height:
3.875 inches
Overall Width:
2.875 inches
Unthreaded Mounting Hole Diameter:
0.221 inches
Bulb Length:
3.813 inches
Bulb Diameter:
0.500 inches
Longest Horizontal Distance Between Mounting Centers:
1.375 inches
Shortest Horizontal Distance Between Mounting Centers:
0.688 inches
Longest Vertical Distance Between Mounting Centers:
2.250 inches
Tamanantana Oanaina Flamant Taman
Tempurature Sensing Element Type:
Bulb
Bulb
Bulb Mounting Method:
Bulb Mounting Method: Bracket and unthreaded hole
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle Contact Adjustability:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle Contact Adjustability: Actuation point not adjustable
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 250.00 actuation point degrees fahrenheit
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 250.00 actuation point degrees fahrenheit Media For Which Designed:
Bulb Mounting Method: Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Connector, receptacle Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 250.00 actuation point degrees fahrenheit Media For Which Designed: Gas or liquid

--

NSN 5930-00-613-1992

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0